



Key Features:

- Capacitive key pad touch buttons
- Weatherproof outdoor design
- RS485 communication interface



Technical Specifications:

| Name | Details |
|-------------------------|--|
| Input Voltage | 9-24VDC |
| Communication Interface | RS485 |
| Communication standards | 125kHz, 13.56MHz (MIFARE Classic/Ultralight) |
| Button | Push button capacitive touch |
| Indicators | Red/Green LED, buzzer |
| Operating temperature | -20 - 70C |
| Configuration methods | Factory configured |
| Cabling | Cat5e/Cat6 up to 100m |
| Housing | Metal, Plastic |
| Color | Silver |
| Dimension | 158mm(H)x55mm(W)x30mm(D) |

Operating Instructions:

The reader must be connected to the GymMaster Gatekeeper access control unit. A member of the facility who Has the rights to access the door can enter their pin followed by the '#' or present their key fob to the reader. The access control unit will then verify the access and let the reader respond with the following:

- If the access is granted, the reader will flash green and beep once.
- If the access is denied, the reader will flash red and make a deny sound.
- On idle, the reader will flash green from time to time.

Wiring instructions:

The reader uses RS485 communications and comes pre-wired for testing. Below shows what the wires correspond to:



It is recommended to use dedicated data cable, cat5e or cat6, over a maximum of 100 meters (110 yds). Wiring instructions can be found in: https://gymmaster.com/hardware-documents

If you require any help or encounter any issues, please contact GymMaster